


Lightning current and surge arrester, 3-pole



V 50-B+C/...: Combination arrester set, lightning and surge arrester Type 1+2 to DIN EN 61643-11 (B+C to VDE 0675 Part 6).

- For lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity 12.5 kA (10/350) per pole
- Universally suitable for TN-C systems
- With new Multibase base with multi-connection terminals
- Complete unit, consisting of cover and base, pre-mounted and ready for connection
- arrester, connectable with dynamic cut-off unit
- With visual function display
- Voltage protection level < 1,3 kV
- Encapsulated, non-extinguishing zinc oxide varistor arrester for use in distributor housings
- Labelled connections


Dimensions



Application: Equipotential bonding in buildings, even those with external lightning protection of Class III and IV, and in standard distributor housings.

Type	Highest continuous voltage V	Version	Pack. pcs	Weight kg/100 pcs.	Item No.
V50-B+C 3-280	280	3-pole	1	42,300	5093627

Connection options



V50-B+C 3-280

Nominal voltage V	U _N	230
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350) kA	I _{imp}	12,5
Total discharge current (10/350) kA	I _{total}	37,5
Nominal discharge current (8/20) kA	I _n	30
Arrester surge current (8/20) [total] kA	I _{total 8/20}	90
Maximum discharge current (8/20 μs) kA	I _{max}	50
		—
Voltage protection level kV	U _p	< 1,3
Response time ns	t _A	<25
Maximum back-up fuse A		125
Temperature range °C	θ	-40-80
Division unit TE (17.5 mm)		3
Protection rating		IP20
Connection cross-section rigid mm ²		2,5-35
Connection cross-section, multi-wire mm ²		2,5-35
Connection cross-section, flexible mm ²		2,5-25